



MATERIAL SAFETY DATA SHEET

1. We would like to inform our customers that these batteries are exempt articles and are not subject to the 29 CFR 1910.1200 OSHA requirements, or to the Canadian WHMIS requirements and the sheets are supplied as a service to you. For other MSDSs and related information, visit: <http://www.rayovac.com/technical/msds.htm>

1. IDENTIFICATION

PRODUCT NAME: Lithium Carbon Monofluoride Batteries (BR)

SIZES: Consumer AA and D sizes

EMERGENCY TELEPHONE NUMBER: 800-424-9300 (24 hr, Chemtrec)

Environmental Health & Safety Information: 608-275-4846

EDITION DATE: 07-19-2010

APPROVED BY: Kevin J. Domack

2. INGREDIENTS

INGREDIENT NAME	CAS #	%	TLV**/TWA
Aluminum (as metal)	91728-14-2	8-12	15 mg/m3 as dust*
Steel (as metal) and plastic	--	21-44	None established
Carbon Monofluoride	51311-17-2	18-35	3.5 mg/m3 as carbon
Carbon Black	1333-86-4	1-3	3.5 mg/m3 (TWA respirable**)
Nickel as (metal)	7440-02-0	0.3-2	1.0 mg/m3**
Propylene Carbonate	108-32-7	7-11	None established
Dimethoxyethane (1,2)	110-71-4	7-11	None Established
Lithium	7439-93-2	5-93	None Established
Lithium Tetrafluoroborate	14283-07-9	1-3	None Established
Polyvinilidene Fluoride	24937-79-9	0.5-2	2.5 mg/m3 as Fluorides*

*Source: OSHA 29 CFR 1910.1000 Table Z-1, 2 or 3 3-01-2010 **Source: ACGIH 2006 TLV's and BEI's

3. PHYSICAL DATA

Boiling Point @ 760 mm Hg (°C):	NA
Vapor Pressure (mm Hg @ 25°C):	NA
Vapor Density (Air = 1):	NA
Density (grams/cc):	NA
Percent Volatile by Volume (%):	NA
Evaporation Rate (Butyl Acetate = 1):	NA
Physical State:	NA
Solubility in Water (% by Weight):	NA
pH:	NA
Appearance and Odor:	cylindrical assembled and sealed solid product – AA and D sizes

4. FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NA LOWER (LEL): NA

FLAMMABLE LIMITS IN AIR (%): NA UPPER (UEL): NA

EXTINGUISHING MEDIA: Use foam, dry powder, Lithex as appropriate.

AUTO-IGNITION: NA

SPECIAL FIRE FIGHTING PROCEDURES: As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products (See section 2). Water will cool the fire but may react with available lithium in the batteries producing flammable hydrogen.

***Do not use water on these batteries if fire fighting within an enclosed area.** Evolving hydrogen may build up and autoignite.

SPECIAL FIRE OR EXPLOSION HAZARDS: DO NOT RECHARGE. As a typical sealed battery they may rupture when exposed to excessive heat. Rupture may expose lithium to moisture causing it to react or release flammable or corrosive materials. Do not accumulate undischarged batteries together.

5. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE (TLV) AND SOURCE: NA

EFFECTS OF OVEREXPOSURE: None in normal use

EMERGENCY FIRST AID PROCEDURES:

Skin and Eyes:

Do not pick up a shorting battery as it may cause a burn. Lithium reacts with moisture, do not pick up a damaged or hot battery with out proper hand protection. Get immediate medical attention when eyes may have been exposed to battery contents from a ruptured battery

Swallowing:

LITHIUM COIN CELL SAFETY NOTICE: Keep lithium coin batteries out of the reach of small children; coin cell batteries can be accidentally ingested. If ingested, these batteries may leak harmful contents causing chemical burns, perforation of soft tissue, and in severe cases may cause death. Lithium coin batteries must be removed immediately if swallowed. Seek medical attention immediately. If you or your doctor suspects that a battery has been ingested-for assistance in the US call the NATIONAL BATTERY INGESTION HOTLINE any time at (202) 625-3333; in Canada call 416-813-5900

For more information, visit: <http://www.nema.org/gov/ehs/committees/drybat/>.

6. REACTIVITY DATA

STABLE OR UNSTABLE: Stable INCOMPATIBILITY (MATERIALS TO AVOID): NA

HAZARDOUS DECOMPOSITION PRODUCTS: NA DECOMPOSITION TEMP.(0°F): NA

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid electrical shorting, puncturing or deforming.
